

聚四氟乙烯/超高分子量聚乙烯管推压机 ▶▶▶

PTFE/UHMWPE Tube/Pipe Ram Extruder Machine

型号 Mode	PFG35-5	PFG150	PFG300	PFG500
设备形式 Equipment Form	立式（从上向下挤出） Vertical（Extrude from top to bottom）			
腔数 Number of Cavity	5 cavities	1 cavity	1 cavity	1 cavity
功率 Power	15 KW	15 KW	22 KW	72KW
外径 Outer Diameter	φ10-35MM	φ20-150 MM	φ150-300 MM	φ300-500 MM
外径公差 Tolerance of OD	0.1-0.2MM	0.1 - 0.5 MM	0.5 - 2 MM	1 - 3MM
壁厚 Wall Thickness	2-20MM	3-50MM	3-50MM	3-50MM
壁厚公差 Tolerance of WTH	0.1MM-0.5MM	0.1MM-0.5MM	0.5MM-2MM	3MM
可生产的管道长度 Available Tube Length	取决于楼层或平台高度 Depends on floor or platform height			
每小时产量 Output Per Hour	8+	8+	10+	13+
电压 Voltage	380V 50Hz 3P	380V 50Hz 3P	380V 50Hz 3P	380V 50Hz 3P
设备重量 Weight of Machine	800KG	1300KG	2000KG	3000KG
设备尺寸 Size of Machine	1.05m*0.7m*2.5m	1.2m*0.7m*2.5m	1.25m*0.8m*3m	1.25m*0.8*3.2m

